

ELECTRONIC FURNACEMETER™ TOUCH



The FurnaceMeter™ is a precision flow measurement instrument designed specifically to meet the rugged requirements of industrial heat-treatment applications.

The FurnaceMeter™ utilizes precision, fieldproven, & certifiable differential pressure flow measurement technology. The advanced calibration and display module includes integrated flowrate alarm and Totalization functions. In addition, every FurnaceMeter™ comes complete with a calibration certificate to meet ISO & QS quality systems.

OPTIONS AVAILABLE:

ELECTRONIC VALVE →



MANUAL VALVE →



NO VALVE →



FEATURES & BENEFITS

- Manual or electronic flow control valve
- Precision flow measurement and control
- NIST Traceable 10 point calibration with every meter
- In-situ calibration certification meets CQI-9 requirements
- Integrated flow alarm (Flow Switch)
- Integrated flow totalizing
- Touchscreen display
- Analog control and feedback signals (4-20 mA)
- Serial communications and configuration software
- No fragile sight glass tubes, oil or float assemblies to maintain
- Retrofit existing flow measurement equipment without additional piping

SPECIFICATIONS

Power	No power required
Ambient Temperature	32°-150° F
Max Inlet Pressure	2 PSI (Standard Model) 40 PSI (HP Model) 250 PSI (HPX Model)
Flow Accuracy	± 4%
Repeatability	2%
Flow Output Signal (linear)	4-20MA
Flow Control Signal (linear)	4-20MA
Flow Output Signal	SPDT Relay
Turndown	15-100%

* Calibration is referenced to standard atmospheric conditions: (70° F, 14.7 PSIA)

USA

+1 414 462 8200
Sales.na@upc-marathon.com

CANADA

+1 514 335 7191
Sales.na@upc-marathon.com

CHINA

+86 21 3463 0376
Sales.mmichina.cn

FRANCE

+33 3 81 48 37 37
Sales.fr@upc-marathon.com

GERMANY

+49 7161 94888 0
Sales.de@upc-marathon.com

POLAND

+48 32 296 66 30
Sales.pl@upc-marathon.com